



A: 1004 ft	Index: 1.467700	[H]: 100ns / 32.8ft
B: 1326 ft	2-Point Loss: 0.212 dB	Avg: Fast 256
A -> B: 322 ft	Reflectance: -67.08 dB	340M-57/1310 nm/SM

----- Page 1 -----
 [Cable I.D.: WGC One]
 [Fiber No.: 1 Fiber Type: SM]
 [Sheath Length: 325]
 [Test Site: Main Office]
 [Far Site: Branch Office]
 [Date: 01-07-08 (mm-dd-yy)]
 [Operator: WGC Technician]
 [Notes:]
 []
 []

Primary Trace: RHU1-3A.TRX Trace Parameters:
 Date: 1/7/08 Mode: N/A
 Time: 01:20 PM Range: 13123 ft
 Product Type: Corning 340 Resolution: 0.82 ft
 Opt. Module: 340M-57 Pulse Width: 100 ns
 Fiber Type: Singlemode WaveLength: 1310 nm
 FAS Thresholds: Index: 1.467700
 Loss: 0.00 dB Horz. Shift: 0 ft
 Reflectance: 0.00 dB Vert. Shift: 0.00 dB
 Fiber Break: 0.00 dB No. Averages: 256
 Backscatter: -77.0 Trace Type: T5(T5)
 Trace Flags:
 ORL: N/A